



MAST CAMERA 200 HD

BWR REFUELING MACHINE CAMERA

The Mast Camera 200 HD is a high radiation tolerant camera designed for permanent or temporary installation on a BWR refueling machine mast. It enables the machine operator to read the serial number on the upper tie plate / bail handle. It also helps the operator to view the lower tie plate / nose cone area when guiding the fuel back through the top guide. The Mast Camera 200 HD is excellent in a BWR for supervision during fuel handling and core mapping.

APPLICATIONS

- · Supervision during fuel handling
- · Core mapping

BENEFITS

- The new Mast Camera 200 HD can easily be incorporated to an existing Mast Camera system
- Auto-positioning functions of zoom, tilt and focus
- 4 lights aimed at fuel assembly lower end at 4-5m (13-16 ft), 2 lights aimed at gripper at 0,5-1,0m (1.6-3.3 ft)
- 10x more light sensitive than previous Mast Camera version

SPECIFICATIONS

| Dimensions (L*W*H) | 264x147x138 mm (10.4"x5.8"x5.4") |
|--|---|
| Water tightness | 3 bar, (30 m, 98 ft) |
| Maximum temperature | 50°C (122°F) |
| Weight | 5.8 kg (12.8 lbs) |
| Zoom | x10 optical x4 digital giving x40 |
| Housing material | Stainless steel EN 1.4303 anodized aluminum |
| Lights | 6 x LED, in total 5400 lumen |
| Resolution HD version | 1080p, 25/30 fps |
| Radiation tolerance (total dose) | 10 000 Gy (1 000 000 rad) |
| Radiation tolerance (dose rate) | 1 000 Gy/h (100 000 rad/h) |

We reserve the right to alter specifications without prior notice



MAST CAMERA 200 HD IMAGES







We reserve the right to alter specifications without prior notice

US office | Phone: +1 910-399-4240 Email: us@ahlbergcameras.com Service office | Phone: +46 176 20 55 00 Email: rd@ahlbergcameras.com