



# PT265

FHD PAN-AND-TILT UNIT FOR THE CCTV90/95/98 and CCTV116 CAMERAS

[ahlbergcameras.com/products/accessories/pt265](http://ahlbergcameras.com/products/accessories/pt265)



The PT265 is a pan-and-tilt unit for the CCTV90/95/98 and CCTV116 cameras with FHD capability. It seamlessly regulates its movements and can be equipped with potentiometer for pan-and-tilt registration.

## MORE INFORMATION ABOUT PT265

### APPLICATIONS

- Pan-and-tilt unit for use with CCTV90/95/98 and CCTV116

### BENEFITS

- High radiation tolerance
- Robust design
- Seismically certified
- Can be equipped with potentiometers for pan-and-tilt registration

## SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

|                  |                 |
|------------------|-----------------|
| Width            | 395 mm          |
| Length           | 198 mm          |
| Height           | 554 mm          |
| Weight           | 34 kg           |
| Housing material | Stainless steel |

### MECHANICAL FEATURES

|            |                               |
|------------|-------------------------------|
| Pan Angle  | 324° (adjustable 84° to 360°) |
| Tilt Angle | 180° (90-0-90°)               |

### ENVIRONMENTAL TOLERANCES

|                                  |                                                                                                 |
|----------------------------------|-------------------------------------------------------------------------------------------------|
| Temperature Range                |                                                                                                 |
| Radiation tolerance (total dose) | 1 000 000 Gy (100 000 000 rad) without positioning. 50 000 Gy (5 000 000 rad) with positioning. |

*We reserve the right to alter specifications without prior notice*

## PT265 IMAGES



*We reserve the right to alter specifications without prior notice*