

PT265

FHD PAN-AND-TILT UNIT FOR THE CCTV90/95/98 and CCTV116 CAMERAS

ahlbergcameras.com/products/accessories/pt265

The PT265 is a robust pan-and-tilt unit for the CCTV90/95/98 and CCTV116 cameras with FHD capability. It seamlessly regulates its movements and can be equipped with potentiometers for pan-and-tilt registration, and for recall of memorized positions.

MORE INFORMATION ABOUT PT265

APPLICATONS

- Pan-and-tilt unit for use with CCTV90/95/98 and CCTV116

BENEFITS

- High radiation tolerance
- Robust design
- Seismically certified
- Can be equipped with potentiometers for pan-and-tilt registration

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width	395 mm
Length	198 mm
Height	554 mm
Weight	34 kg
Housing material	Stainless steel

MECHANICAL FEATURES

Pan Angle	324° (adjustable 84° to 360°)
Tilt Angle	180° (90-0-90°)

ENVIRONMENTAL TOLERANCES

Temperature Range	
Radiation tolerance (total dose)	1 000 000 Gy (100 000 000 rad) without positioning. 50 000 Gy (5 000 000 rad) with positioning.

We reserve the right to alter specifications without prior notice

Main office | Phone: +46 176 20 55 00
Email: main@ahlbergcameras.com

US office | Phone: +1 910-399-4240
Email: us@ahlbergcameras.com

Service office | Phone: +46 176 20 55 00
Email: rd@ahlbergcameras.com

PT265 IMAGES











We reserve the right to alter specifications without prior notice

Main office | Phone: +46 176 20 55 00
Email: main@ahlbergcameras.com

US office | Phone: +1 910-399-4240
Email: us@ahlbergcameras.com

Service office | Phone: +46 176 20 55 00
Email: rd@ahlbergcameras.com