



## Cable Reel 560

## CAMERA CABLE REEL WITH SLIP RINGS ahlbergcameras.com/products/cables/cable-reel-560



The Cable Reel 560 is a cable reel with slip rings used for camera cables. It is designed for fixed installation with placement on locations such as a refueling machine or fuel bridge.

# MORE INFORMATION ABOUT CABLE REEL 560

#### **APPLICATIONS**

• For fixed installation on refueling machines and fuel bridges

#### **BENEFITS**

- Automatic tension control during winding and unwinding
- · Equipped with ratchet
- Integrated camera cable connectors
- Specially designed for prolonging the camera cable lifetime through eliminating cable twisting in more than one direction
- Motorized cable reel is optional

#### **SPECIFICATIONS**

#### PHYSICAL CHARACTERISTICS

Drum Diameter	300 mm
Outer Diameter	550 mm
Maximum Cable Length	40 m
Weight Without Cable	35 kg
Width	324 mm
Slip Rings	Yes
Motorized Cable Reel	Speed and torque depends on payload and cable length, 30kg payload = 0,2 m/s Powered by 2A@24VDC Position feedback and memorized positioning possible

We reserve the right to alter specifications without prior notice

Email: rd@ahlbergcameras.com

Service office | Phone: +46 176 20 55 00



### **CABLE REEL 560 IMAGES**
















We reserve the right to alter specifications without prior notice