



Camera Cable T37

HD and SD CAMERA CABLE

ahlbergcameras.com/products/cables/camera-cable-t37



The T37 camera cable is a robust triple-coax camera cable designed for HD and SD cameras. It is a strong and flexible cable specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

MORE INFORMATION ABOUT CAMERA CABLE T37

APPLICATIONS

Cable for underwater use or in air together with Ahlberg Cameras HD and SD cameras

BENEFITS

- Equipped with a reterminable connector for use in air and a moulded connector for underwater use
- Specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width	12 mm
Minimum Bend Radius, Flexible Installation	80 mm
Outer sheath	PUR, frosted
Color	Black
Weight	0.23 kg/m, 0.15 lbs/ft
Tensile Strength	5000 N
Number of conductors	34 + 3 coaxial

ENVIRONMENTAL TOLERANCES

Radiation Tolerance (total dose)	2 000 000 Gy (200 000 000 rad)
Temperature Rating	-40°C to +80°C (-40°F to +176°F)
Ingress Protection	IP68 (underwater part)
Water Tightness	3.5 bar

We reserve the right to alter specifications without prior notice

Email: rd@ahlbergcameras.com

Service office | Phone: +46 176 20 55 00



CAMERA CABLE T37 IMAGES



We reserve the right to alter specifications without prior notice